TRACKING# 61918	STATË OF TEXAS WELL REPORT	Date Entered: 7/4/2005
OWNER: BOLD SPRINGS W.S.C.	OWNER P.O.B OX 427 ADDRESS: WEST ,	, TX 76691
ADDRESS OF WELL'S LOCATION:	4640 6976715 = 40 16 7	205
COUNTY: McLennan LATITUDE: 514	149 LONGITUDE: 970720	D \$00
Owner's Well Number: #4	ELEVATION: 698 GU	Grid Number: 40 - 16 - 4
✓ New Well	POSED USE: ☐ Monitor Well ☐ Env. Son Industrial ☐ Irrigation ☐ Injection ☐ Public Supply ☐ De-watering ☐ Rig Son If Public Supply well, were plans submitted.	☐ Geothermal Heat Loop Supply ☐ Stock or Livestock
WELL LOG: DIAMETER O	F HOLE DRILLING METHOD:	
Date Drilling Dia. (in) From Surface Started 8/20/2004 28 Surface Completed 7/1/2005 17.5 33	Billien Line	Tool Hollow Stem Auger Bored Reverse Circulation Other
	ANNULAR SEAL DATA	t. #Sacks + Material 775 CEMENT
BOREHOLE COMPLETION: ☐ Open Hole ☐ Underreamed ☐ Oth ☐ Straight Wall ☐ Gravel Packed Gravel Packed Interval from ft. to Size SURFACE COMPLETION: ☐ Surface Slab Installed ☐ Pitless Adap ☐ Surface Sleeve Installed ☐ Alternative F	From ft. to ft Method Used PRESSURE C Cemented By JET STAR Distance to Septic System Distance to Property Line: Method of Verification TA Procedure Used	150 80 ABOR & ASSOC
WATER LEVEL:	Approved by Variance No.	
Static Level 680 ft. below land surface Artesian Flow gpm.	PLUGGING INFO: Well Plugged within Casing left in well:	48 hours Cement/Bentonite left in well:
TYPE OF PUMP: ☐ Turbine ☐ Jet ✓ Submersible ☐ Other Depth to pump bowls, cylinder, jet, etc.	From (ft.) To (ft. F	From (ft.) To (ft.) Cem/Bent Sacks Used: てくその # ほ/5!
WELL TESTS:	PACKERS:	
Type of test: ✓ Pump ☐ Bailer ☐ Jo Yield: 300 gpm with 275 ft. drawdow		Depth
WATER QUALITY:	TD	
Did Driller knowingly penetrate any strata contained undesirable constituents?	which ☐ Yes ☐ Type of water: N/A ☐ Depth of Strata: Chemical Analysis made	de? ✓ Yes □ No
COMPANY NAME: WATTS DRILLING CO ADDRESS 14310 HWY 377 S Name as Signature TIM WATTS	WELL DRILLER FT. WORTH TX 76126 Registered Driller Apprentice	R'S LICENSE NO. 2457

Driller Comments

McLennan 40-16-705

WELL REPORT CONFIDENTIALITY NOTICE

TEX. OCC. CODE Title 12, Chapter 1901.251, authorizes the owner (owner or the person for whom the well was drilled) to keep information in Well Reports confidential. The Department shall hold the contents of the well log confidential and not a matter of public record if it receives, by certified mail, a written request to do so from the owner. Please include the report's Tracking number on your written request.

Texas Department of Licensing Regulation Water Well Driller/Pump Installer Section P.O. Box 12157 Austin, TX 78711

Toll free (800)803-9202 (512)463-7880 FAX (512)463-8616

Email address: water.well@license.state.tx.us Web address: www.license.state.tx.us

DESCRIPTION AND COLOR OF FORMATION MATERIAL

218 Twant

From (ft.) To (ft.) Description

000 - 020 SAND

020 - 170 GREY SHALE AND LIME

170 - 250 GREY SHALE

250 - 420 BLACK SHALE

420 - 750 LIME AND GREY SHALE

750 - 900 GREY SHALE AND LIME

900 - 1600 LIME WITH LIGHT SHALE STREAKS

1600 - 1740 SANDY SHALE

1740 - 1844 SAND

1844 - 1900 SANDY SHALE

1900 - 1910 YELLOW SHALE

CASING, BLANK PIPE, AND WELL SCREEN DATA

Dia. New/Used Type Setting From/To Gage 20 NEW STEEL 0/33 0/1330 13 3/8 NEW STEEL 10 3/4 NEW STEEL 1225/1880 8 5/8 NEW **STEEL** 1880/1910 PIPE IS GUN PERFORATED AT THE FOLLOWING DEPTHS: 10 3/4 PERFORATED FROM 1690/1696 1728/1748 1756/1780 1792/1844

TWO SHOTS PER FOOT WERE INSTALLED AT INTERVALS ABOVE.